

Heavyweight

INSTALLATION & MAINTENANCE

GENERAL INSTALLATION GUIDELINES

1. Read all instructions prior to installation. Follow all guidelines for a successful installation.
2. It is the responsibility of the installer to ensure that products are installed correctly in accordance with all applicable guidelines. Refer to the Heavyweight warranty for any questions about the suitability of a product for any application.
3. It is important to work out of several cartons to mix the patterns when installing Heavyweight to properly mix the décor and ensure a beautiful application.
4. Eastern Flooring Products® produces Heavyweight to imitate natural color and texture variation, but there are a finite number of unique pieces. Therefore, it is necessary to pay attention to avoid creating unintended patterns by installing identical pieces beside one another.
5. Avoid creating patterns with the end joints of the material. Stagger the first piece of each row in size to avoid the end joints of alternating rows from lining up. No pieces smaller than ¼ of the piece in length should be installed to maintain the structural integrity of the floor. End joints in adjacent rows should be a minimum of 12" from one another.
6. Take note of directional arrows on the back of the piece. These arrows should all be pointing the same direction in the installation. For herringbone or other patterned installations, pieces of the same orientation should all be pointing the same direction.
7. All pieces should be thoroughly inspected prior to installation. Installation of material constitutes acceptance of physical and/or aesthetic imperfections. If you have any concerns about the product, please contact your point of purchase. Flooring that has been cut or installed is not eligible for returns
8. Acclimate Heavyweight for a minimum of 24 hours prior to installation. Material that has been stored in areas warmer than 85°F or cooler than 55°F should be acclimated an additional 24 hours prior to installation. The purpose of acclimation is to get the material to the same temperature as the installation space. To acclimate material, place material in stacks of no more than 2 cartons in the installation area after HVAC has been running at normal temperatures in a completely enclosed installation space for at least 48 hours. Be sure that material is out of the path of direct sunlight, heaters, or air vents to ensure proper acclimation.
9. Install Heavyweight in indoor areas that with a constantly maintained temperature between 55°F and 85°F. Eastern Flooring Products® does not recommend this product in 3 season rooms.
10. It is important to protect Heavyweight from exposure to direct sunlight. Direct sunlight can result in thermal expansion, UV fading, and discoloration. Ideal protection will include UV treated windows and the use of drapes/blinds during peak sunlight hours.

Heavyweight

INSTALLATION & MAINTENANCE

11. Eastern Flooring Products® recommends installing Heavyweight after all other trades have completed their work to avoid damaging or soiling the floor.
12. Install Heavyweight with Eastern Flooring Products® recommended Adaptable adhesive, following the additional guidelines provided for that product.

GENERAL SUBFLOOR GUIDELINES

1. Before beginning installation, read all subfloor guidelines for the correct subfloor type. Proper subfloor preparation is the responsibility of the installer and one of the most important components of the durability of any floor.
2. Subfloor must be level, flat, smooth, clean, dry, and structurally sound. Subfloor flatness must be within 3/16" in 10' or 1/8" in 6' in all directions.
3. Subfloor must be free of any dust, solvent, wax, asphalt sealing compound, and other material that may compromise the bonding of the flooring or adhesive. Unevenness and obstructions may compromise the durability and appearance of the floor.
4. Any patching or leveling compound used to achieve a smooth and flat subfloor needs to meet subfloor alkalinity and moisture standards. Eastern Flooring Products® recommends the use of a water resistant, non-shrinking, Portland leveling compound with a compressive strength of at least 3,000 psi.
5. Adaptable adhesive installation instructions may contain additional subfloor standards. Be sure to consult all related instructions prior to installation.
6. Heavyweight is waterproof, but it is not a vapor barrier. Subfloor moisture can still cause mold, mildew, and other moisture-related issues, unrelated to Heavyweight. It is the responsibility of the installer to ensure the subfloor is not improperly emitting moisture prior to installation.
7. Acceptable subfloor types include:
 - a. Concrete slab meeting updated ASTM F710 guidelines
 - b. APA rated plywood underlayment meeting updated ASTM F1482 guidelines
 - c. Underlayment grade particleboard, when properly prepared
 - d. Securely fastened hard surface floors including hardwood, ceramic tile, or one layer of non-cushion backed resilient sheet or tile. Must be clean, smooth, flat, free of deflection, and securely adhered or fastened. Properly prepared resilient tile must be stripped of any wax or coating that could inhibit the adhesive's bond.
 - e. Properly prepared and sealed gypsum cement with a dry density exceeding 90 pounds per cubic foot.

Heavyweight

INSTALLATION & MAINTENANCE

- f. Eastern Flooring Products® recommends AMB2000 for installations requiring assistance in moisture mitigation, bonding, or acoustical performance. AMB2000 can be loose laid and have Heavyweight glue to it in residential and non-rolling load bearing commercial applications. For rolling loads and heavy commercial applications Eastern Flooring Products® requires a double glue application. See AMB2000 documentation for more details.
- 8. Unacceptable subfloor types include, but are not limited to:
 - a. Crumb rubber underlayment, as it may interact with the flooring, chemically.
 - b. Existing floating flooring or cushion back products of any kind. Soft layers of flooring under Heavyweight may compromise the installation integrity and resistance to indentation.
 - c. Ceramic tile with grout joints. Grout joints must be filled with an acceptable patching compound, previously described.
 - d. Carpet of any kind
 - e. Wood adhered to concrete, including sleeper construction subfloors
 - f. Unapproved underlayment with or without express designation as being acceptable for LVT installations.

CONCRETE SUBFLOOR GUIDELINES

- 1. Concrete subfloors must meet the updated ASTM F710 guidelines, prior to installation.
- 2. New concrete floors should be fully cured prior to installation. Concrete slabs must have no visible moisture.
- 3. Concrete subfloors should be free of any adhesive residue. If adhesive residue is cut-back, it must be removed by safe methods such as mechanical removal or wet scraping. Contact a professional to remove these adhesives as breathing crystalline silica or asbestos fibers can cause cancer and is a severe respiratory hazard. Refer to the Resilient Floor Covering Institute's guide "Recommended Work Practices for Removal of Resilient Floor Coverings" for more information on safe removal of resilient flooring.
- 4. Conduct moisture and pH testing prior to installing any floor to limit liability. Ensuring acceptable moisture levels and retaining test records for Heavyweight are the responsibility of the installer. Eastern Flooring Products® is not liable for moisture related claims that do not meet stated installation standards.
 - a. ASTM 1869 Calcium Chloride – maximum result 8 lbs
 - b. ASTM 2170 Relative Humidity – maximum result 90% per 1000 sf per 24 hours
 - c. Concrete pH should be no less than 7, but not exceed 10

Heavyweight

INSTALLATION & MAINTENANCE

WOOD SUBFLOOR GUIDELINES

1. Wooden subfloors must meet the updated ASTM F1482 guidelines, prior to installation.
2. Be certain the floor joists do not impede the floor flatness as required. Floors must be sufficiently rigid to avoid excess deflection. An additional layer of APA rated 1/4" thick underlayment is recommended to aid rigidity where unacceptable conditions exist.
3. Crawl spaces and basements must be dry. The bottom of wooden subfloor joists must be a minimum of 18" above ground surface. A 6 mil or greater black polyethylene sheeting must be in place covering 100% of the ground and overlapping a minimum 6" at seams acting as a moisture barrier. This polyethylene sheeting must run up the walls no less than 6". Air venting must be open on all sides and open no less than 1.5% of the total crawlspace area.
4. Plastic sheeting is not recommended over wood subfloors.

RADIANT HEAT GUIDELINES

1. Embedded radiant heating elements are acceptable in the subfloor provided they are a minimum of 1/2" from Heavyweight in final installation.
2. Material covering embedded radiant heating elements should still meet subfloor standards.
3. To install Heavyweight over radiant heating systems, system should be running and operational for at least 2 weeks prior to installation. 24 hours before, during, and after installation, system should be turned off. Failure to do so will shorten the working time of the adhesive. After installation, increase temperature in increments of 5°F per hour to avoid overheating. Once installed, the floor temperature should never exceed 85°F.

INSTALLATION INSTRUCTIONS

1. Read all subfloor guidelines prior to installation. Ensure all areas of installation meet all requirements. Eastern Flooring Products® is not responsible for floor failures resulting from subfloors that do not meet listed requirements.
2. Thoroughly inspect all pieces and pattern prior to installation. Eastern Flooring Products® is not responsible for installation related costs when visibly defective pieces are installed.
3. Measure and designate the middle of each wall. Strike a chalk line between the center of each wall in a square or rectangular room to determine the center of the room. Layout the room with the longest side of the plank perpendicular to the longest wall in the room, or parallel to incoming sunlight in square rooms. Both the first and last row should be greater in width than 1/2 the width of the piece, so you may need to adjust the center point of your installation pattern

Heavyweight

INSTALLATION & MAINTENANCE

and/or rip the pieces for these rows.

4. Working from multiple cartons, dry lay several rows of material to ensure desired aesthetic. Dry-fit your rows to ensure the starting and ending pieces of each row are no less than $\frac{1}{4}$ of the length of the total piece. Take care to note and properly position each piece to ensure the arrows on the back are pointing the same direction for all pieces.
5. Consult the Adaptable adhesive recommended trowel size and spread rate. Spread adhesive based on how much area can be installed within the working time using the required tools, described herein.
6. Eastern Flooring Products® recommends using Adaptable on porous or non-porous floors.:
 - a. For a pressure sensitive installation, follow the following steps:
 - i. Wait 30-60 minutes after adhesive is spread to allow it to dry, the adhesive will darken to visually cue the preparedness
 - ii. Be sure to install the material within the working time for the adhesive. While the time will vary based on temperature and humidity, it can be up to 12 hours.
 - b. For a semi-wet set installation on porous floors, follow the following steps:
 - i. Wait 20-30 minutes after adhesive is spread to allow it to skin over.
 - ii. Working time is around 20-30 minutes.
7. Begin installation in the center of the room for best results. Based on your layout from the pre-installation notes, install the first pieces adjacent to your center line.
8. Lay each adjacent piece, ensuring a tight fit to the previous.
9. After laying all rows of material, roll the floor with a 75–100-pound roller to ensure proper adhesive transfer.
10. Install trim over exposed subfloor or unsightly cuts to ensure a beautiful, finished floor.

AFTER INSTALLATION

1. All vinyl floors can be scratched in abusive situations. To avoid scratching your floor:
 - a. All furniture must be equipped with felt pads to avoid scratching the floor. Heavy furniture and appliances must be equipped with non-staining large surface floor protectors. Furniture with wheeled castors should only have 2" or wider castors no less than 4" in diameter.
 - b. Regularly sweep or vacuum floors to keep your floor free of debris. Debris can become trapped in shoes, castors, or other acceptable contacts with floor and create scratches. Do not use vacuums with beater bar attachments on.
 - c. Keep pets' nails trimmed.

Heavyweight

INSTALLATION & MAINTENANCE

- d. Avoid sliding things across the floor that could have rough edges or trap debris.
 - e. Avoid high heeled shoes as they can create pressure of over 500PSI which may scratch or indent floors.
2. Eastern Flooring Products® recommends equipping all office chairs with soft, non-marking, roller blade style wheels to avoid damaging the floor. Do not use ball-type castors.
 3. Floating floors must not be pinned with fixed cabinetry, heavy equipment, or other heavy items. This includes kitchen cabinets/islands, slate pool tables, safes, or other heavy objects that would keep the floor from floating freely. If you have a question about a given piece of furniture or otherwise heavy object, please contact point of sale.
 4. Furniture should be moved onto the newly installed floor using an appliance hand truck only after Adaptable's recommended waiting period for heavy rolling traffic.
 5. Oil or petroleum-based products can result in surface staining. Do not track asphalt driveway sealer or other oil-based products on the floor.
 6. Use walk-off mats at entrances to prevent dirt, grit, and staining substances from damaging the floor. Use mats with non-staining backs, as rubber may discolor the floor.
 7. Eastern Flooring Products® does not recommend the use of steam cleaning devices of any sort, abrasive cleaners, harsh chemicals, detergents, or "mop and shine" products. If you have a question about care and maintenance, consult the Eastern Flooring Products® Care and Maintenance Guide.

REPORTING A PROBLEM

1. If you think there is something wrong with your floor that is covered by this warranty, immediately contact the company you purchased the floor from within 48 hours of noticing the problem. Subsequent damage to the floor is not covered by the warranty.
2. Do not walk or roll anything over the affected area of the floor until the problem is identified or resolved.
3. If the company you purchased the product from determines there is a warranted issue with the floor, they will contact Eastern Flooring Products® to file a claim. They are the only party that can file a claim or inquire as to the status of that claim.
4. Eastern Flooring Products® has the unimpeachable right to decline a claim if not given the opportunity to inspect the floor in a timely manner. Floors that have been repaired, replaced, or permanently covered without manufacturer inspection will not be eligible to file a claim or receive compensation.

WARNING: Existing resilient floor coverings and black asphalt adhesive may contain asbestos. Improper removal procedures could release asbestos fibers into the air. Asbestos fibers, when inhaled, could cause serious bodily harm. Do not sand or dry scrape these materials. If removal of existing floor coverings is necessary, be certain that all precautions are taken and proper procedures are followed. For information regarding proper removal procedures in the U.S.A., please consult the Resilient Floor Covering Institute (966 Hungerford Drive, Suite 12-B, Rockville, MD 20850) for a pamphlet, "Recommended Work Practices for the Removal of Resilient Floor Coverings."